

HYDRANT UNDERGROUND / 7150



PN 16
DN80 → DN100

PRODUCTION STANDARDS

DESIGN	TS EN 14339
END CONNECTION	FLANGED TS EN 1092-2 / ISO 7005-2
TEST	TS EN 14339
MARKING	TS EN 19

MATERIAL SELECTION

BODY	EN-GJL-250 CAST IRON (GG25) EN-GJS-400 DUCTILE IRON (GGG40) EN-GJS-500 DUCTILE IRON (GGG50)
PLUG	ALUMINUM-BRASS
STEM	1.4021 - AISI 420 STAINLESS STEEL
SEALING	EPDM
COATING	ELECTROSTATIC POWDER EPOXY

FEATURES

- FAF7150 Underground hydrant is provided water to fire brigade crew at possible fire moment to treat rapidly.
- The body of hydrant is underground and the cover is overground. It is vertical to ground and has one outlet.
- It is designed and manufactured according TS EN 14384 standarts.
- It can be engaged easily and quickly. It is opened and closed due to hydrant switch by rotating the control shaft, which is at the head of hydrant.
- Remaining water, which is in the hydrant after usage, can be released by check valve.
- The hydrant is protected in case of freezing.

APPLICATIONS

Fire Protection

TEMPERATURE

+130 °C