

HBL-OIL-T90

Tazza / Cleat



Caratteristiche della tazza / Cleat characteristics

	Um	Norme / norms	Valore / value
Colore / color			nera / black
Peso / weight	Kg/m		2,4
Diametro min. tamburi / min. pulley diameter	mm		280
Diametro min. ruote deflessione / min. deflection pulley diameter	mm		-

Gomma / Rubber

	Um	Norme / norms	Valore / value
Polimero base / base polymer			SBR/NBR
Durezza / hardness	SH/A	UNI 4916	60
Peso specifico / specific weight	g/cm ³	UNI 7092	1,2
Modulo a 100 % / form to 100%	Mpa		
Carico di rottura / tensile strength	N/mm ²	UNI 6065	> 8,5
Allungamento a rottura / elongation at break	%	UNI 6065	> 350
Perdita all'abrasione / abrasion loss	mm ³	ISO 34 (type B)	< 290
Resistenza alla lacerazione / tear strenght	N/mm	UNI 9185	> 16,5

Tabella Tolleranze / Table Tolerances

	da / from	a / to	Um	tolleranze / tolerances
Durezza / hardness	-	-	SH/A	± 5
Spessore / thickness	-	-	mm	± 0,02
Resa elastica / elastic yield	-	-	%	± 3
Dimensioni / dimensions	-	-		ISO 3302-1-M3

